

# SHINDENGEN

## HVX-2 Series Power MOSFET

N-Channel Enhancement type

**2SK2663**  
**( F1E90HVX2 )**

**900V 1A**


### FEATURES

- Input capacitance (Ciss) is small.  
Especially, input capacitance at 0 bias is small.
- The static Rds(on) is small.
- The switching time is fast.
- Avalanche resistance guaranteed.

### APPLICATION

- Switching power supply of AC 240V input
- High voltage power supply
- Inverter

### OUTLINE DIMENSIONS



### RATINGS

Absolute Maximum Ratings (Tc = 25 )


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T <sub>stg</sub>		-55 ~ 150	
Channel Temperature	T <sub>ch</sub>		150	
Drain-Source Voltage	V <sub>DSS</sub>		900	V
Gate-Source Voltage	V <sub>GSS</sub>		± 30	
Continuous Drain Current (DC)	I <sub>D</sub>		1	A
Continuous Drain Current (Peak)	I <sub>DP</sub>	Pulse width 10 μs, Duty cycle 1/100	2	
Continuous Source Current (DC)	I <sub>S</sub>		1	
Total Power Dissipation	P <sub>T</sub>		10	W
Repetitive Avalanche Current	I <sub>AR</sub>	T <sub>ch</sub> = 150	1	A
Single Avalanche Energy	E <sub>AS</sub>	T <sub>ch</sub> = 25	10	mJ
Repetitive Avalanche Energy	E <sub>AR</sub>	T <sub>ch</sub> = 25	1	

● Electrical Characteristics  $T_c = 25^\circ\text{C}$ 


Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 1\text{mA}, V_{GS} = 0\text{V}$	900			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 900\text{V}, V_{GS} = 0\text{V}$			250	$\mu\text{A}$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 30\text{V}, V_{DS} = 0\text{V}$			$\pm 0.1$	
Forward Transconductance	$g_{fs}$	$I_D = 0.5\text{A}, V_{DS} = 10\text{V}$	0.6	1.0		S
Static Drain-Source On-state Resistance	$R_{DS(ON)}$	$I_D = 0.5\text{A}, V_{GS} = 10\text{V}$		10.5	14	$\Omega$
Gate Threshold Voltage	$V_{TH}$	$I_D = 0.2\text{mA}, V_{DS} = 10\text{V}$	2.5	3.0	3.5	V
Source-Drain Diode Forward Voltage	$V_{SD}$	$I_S = 0.5\text{A}, V_{GS} = 0\text{V}$			1.5	
Thermal Resistance	$\theta_{jc}$	junction to case			12.5	$^\circ\text{C}/\text{W}$
Total Gate Charge	$Q_g$	$V_{DD} = 400\text{V}, V_{GS} = 10\text{V}, I_D = 1\text{A}$		10.5		nC
Input Capacitance	$C_{iss}$	$V_{DS} = 25\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$		230		pF
Reverse Transfer Capacitance	$C_{rss}$			5		
Output Capacitance	$C_{oss}$			23		
Turn-On Time	$t_{on}$	$I_D = 0.5\text{A}, V_{DD} = 150\text{V}, R_L = 300\Omega$		10	18	ns
Turn-Off Time	$t_{off}$			50	85	

# 2SK2663

# Transfer Characteristics




## 2SK2663 Static Drain-Source On-state Resistance




2SK2663 Gate Threshold Voltage



# 2SK2663 Safe Operating Area



# 2SK2663 Transient Thermal Impedance




## 2SK2663 Single Avalanche Energy Derating






# 2SK2663 Capacitance



# 2SK2663

## Single Avalanche Current - Inductive Load



2SK2663

Power Derating



## 2SK2663 Gate Charge Characteristics

